



**THE BASIC FITTING PACKAGE:**

1. TANK ADAPTER WITH A 125# MATING FLANGE AND RADIUSED SADDLE FOR ATTACHMENT TO THE SIDEWALL OF A POLYETHYLENE TANK
2. 0.25" THICK GASKETS FOR SEALING THE TANK ADAPTER TO THE TANK EXTERNALLY AND THE ATTACHMENT HARDWARE TO THE TANK INTERNALLY
3. 1/2" X 3.5" ALLOY CORE-BOLTS WITH PVC ENCAPSULATED HEADS FOR ATTACHING THE FITTING TO THE TANK - CAPS INCLUDED

**FITTING MATERIALS:**

- 304SS\*
- PVC\*
- 316SS
- C-276 (HASTELLOY)
- TITANIUM
- FIBERGLASS

**GASKETS:**

- EPDM\*
- VITON

**ATTACHMENT HARDWARE:**

- 316SS\*
- C-276 (HASTELLOY)
- TITANIUM

**SIZES:**

\*6", \*8", \*10", 12", 14", 16", 18", 20", 24"

\*DENOTES STANDARD INVENTORY

**OPTIONS:**

- INTERIOR PIPE STUB (STANDARD ON PVC FITTINGS)
- CUSTOM FITTING LENGTH
- THREADED CONNECTIONS
- SANITARY CONNECTIONS
- FLAT SADDLES (FOR FLAT SURFACES)
- LONGER CORE-BOLTS (FOR TANKS WITH WALLS ≥ 1.75")
- LARGER SIZES

**NOTES:**

1. THE BASIC FITTING "PACKAGE" INCLUDES EVERYTHING NECESSARY FOR INSTALLATION
2. VERIFICATION OF COMPATIBILITY IS THE BUYER'S RESPONSIBILITY
3. LEAD TIME FOR CUSTOM FITTINGS IS ≤ 2 WEEKS
4. THE PVC FITTING FLANGE IS ANSI 150#

**ATTACHMENT HARDWARE**

Fitting	Quantity
6"	12
8"	16
10"	18
12"	24
14"	24
16"	28
18"	30
20"	32
24"	40



TITLE	
6"-24" RADIUSED TANK ADAPTERS - FLANGED	
SCALE: NONE	DRAWN BY: KH
DATE: 4-17-12	CHECKED BY: SI